



GAMITA PAK-IT PTE. LTD.

164 Kallang Way, #02-07 Kolam Ayer Industrial Estate
Singapore 349248
Homepage: <http://www.gamitapakit.com.sg>
Phone: +65 6842 2686 / +65 6846 0737 Fax: +65 6842 3698



A NEW PRODUCT IN OUR FAMILY WITH “BRUSHLESS MOTOR”!!!

ZP92A & ZP96A



Features:

- **Brushless Motor** - ZAPAK patented single motor design provides extremely long life service
- **Li-Ion Battery** - 18V 3000mAh high capacity rechargeable battery and **Bosch** 30 minutes charger
- Max. tension **400KGs (4000N)** - **96A heavy duty model**
- Max. tension **250KGs (2500N)** - **92A standard duty model**
- **Patented strap gripper designs** contributes to high tension ability
- **One-handed operation** performs automatic tensioning, frictioning welding, and cutting efficiently
- **Pre-programmed touch panel** with digital signal to suit different operation needs instinctively
- **Lightest** model in same class of tools approx. **3.46KG only (7.60lbs incl. battery)** relieves operation fatigue
- **Special tool retreating device** ensures smooth and easy removal of tool
- **Unique rear-end roller** design prevents scratches or worn out damages on strapping objects
- **User self-adjustable strap width guiders** and self-changeable wearing parts
- **Optional hanger** reduces operation fatigue
- **Soft mode device** facilitates lighter strapping tension force for light packages of fragile objects
- One-handed operation conforms to **CE Safety Directives** and meets **ROHS** requirements
- Li-Ion battery complies with **UN38.3** safety requirements
- **Sealing time adjustment:** 0.4 ~ 2.0 secs
- **Li-Ion battery life is up to 2000 charges** with proper charging and discharging habits
- Fully charged Li-Ion battery supports up to **max. 600 cycles (PP)** dependant on straps quality, tension setting and sealing time settings

Model	Battery Charger Voltage	Fits poly strap	Strap Width		Strap Thickness		Tension Range	Sealing Efficiency
			mm	inch	mm	inch		
ZP92A	230V / 240V	PP	9-16	3/8-5/8	0.55 - 1.35	.022 - .053	10-250KG	85±5%
		PET	9-16	3/8-5/8	0.55 - 1.35	.022 - .053		
ZP96A	230V / 240V	PP	16 & 19	5/8 & 3/4	0.75 - 1.35	.029 - .053	40-400KG	
		PET	16 & 19	5/8 & 3/4	0.65 - 1.35	.026 - .053		

Remarks:

* Tension performance and sealing efficiency vary based on battery capacity, strap specification and quality.

* Softer and thinner strap may require different cutter. Please provide us with these data.