



A compact TIJ coder performs versatile functions beyond your expectation, coding even with connectivity is essential, it can do more is worth your exploration.



Technology	TIJ2.5
Power requirement	AC110-220V 50/60HZ
Display	7" Color LCD with LED backlight
Operating temperature	5°Cto 45°C (41°F – 112°F)
Controller operating system	Linux
Message storage	Up to 999 messages
Coding head controlled ability	Two TIJ2.5 coding heads
Coding line	1- 8 lines
Coding height	Selectable font size from 1mm to 12.7mm
Coding speed	Up to 90m/min
Max. Coding length	1 meter
Coding resolution	Max. 600dpi x 600dpi. Regular 300dpi x 600dpi
Coding distance	Recommended 6mm
Coding Capability	Alphanumeric, logos, date/time, shift code, counter, lot box code, GS1 barcodes, database and 27 languages for entering to code.
User interface	WYSIWYG. Multiple-language available (some may need translation)
External data interface	RS232, USB, Ethernet
Database coding format	CSV
Coding head data line	Standard 75cm, maximum 200cm
Weight	Controller 820g(Excluding bracket) Print head 380g(Excluding cartridge and bracket)
Dimension(L/W/H)	Controller 205x140x68 (mm) 8.1x5.5x2.7(inches) Print head 130x115x94(mm) 5.1x4.5x3.7(inches)
Optional	Encoder, bulk supply, backstage analysis/manage software



GAMITA PAK-IT PTE. LTD.

7 Gambas Crescent #07-25 ARK@Gambas
Singapore 757087
Phone: (065) 6846 0737, 6842 2686 , Fax: (065) 6842 3698
Email: sales@gamitapakit.com.sg
Website: <http://www.gamitapakit.com.sg>

YOUR NEAREST SERVICE PROVIDER:

